


Univers	Professional
Type	Products
Category	Ropes
Subcategory	Low Stretch Ropes




## AXIS 11 mm


The AXIS 11 mm low stretch kernmantel rope is designed for work at height. The standard diameter ensures a good grip for easier handling. The EverFlex technology guarantees great flexibility and consistent performance over time. Rope available in six colors and four lengths.



The standard rope diameter ensures a good grip for easier handling.



EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain consistent handling and optimal performance with devices.



It is possible to order a rope of a specified length.



The addition of sewn terminations manufactured on one or both ends provides a ready-to-use rope. These terminations have a protective sheath that keeps the connector in position and facilitates handling.

---

Short Description    Low stretch kernmantel rope with good handling for work at height

---

Selling Points

- Standard diameter ensures a good grip for easier handling
- Consistent performance over time:
  - construction with nylon core and polyester sheath, with specific weave
  - EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain excellent handling and optimal performance with devices
- Available in six colors: white, yellow, black, blue, red and orange
- Standard lengths: 50, 100, 200 and 500 m
- Customization on request:
  - option of ordering a rope of a specified length (up to 700 m)
  - addition of sewn terminations manufactured on one or both ends, providing a ready-to-use rope. These terminations have a protective sheath that keeps the connector in position and facilitates handling. They are also stronger than a figure-eight knot





---





Specification





- Diameter: 11mm
- Material(s): polyester, nylon
- Certification(s): CE EN 1891 type A, UKCA, EAC, NFPA 2500 Technical Use, XF 494: FZL-S-Q11, ANSI Z459.1
- Weight per meter: 82g
- Strength tied with figure-eight knot: 19kN
- Strength with sewn termination: 22kN
- Impact force (factor 0,3): 5,2kN
- Number of factor 1 falls: 12
- Construction: 32 carrier
- Percentage of sheath: 41%
- Static elongation: 3%





---




## Specifications by reference

Reference(s)	R074AA03	R074AA04	R074AA05	R074AA38
				
Length	50 m	50 m	50 m	50 m
Color(s)	white	yellow	black	blue
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	2	2	2	2
EAN	3342540816091	3342540816107	3342540816114	3342540822856

Reference(s)	R074AA39	R074AA40	R074AA09	R074AA10
				
Length	50 m	50 m	100 m	100 m
Color(s)	red	orange	white	yellow
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	2	2	1	1
EAN	3342540822863	3342540822870	3342540816152	3342540816169

Reference(s)	R074AA11	R074AA12	R074AA13	R074AA14
				
Length	100 m	100 m	100 m	100 m
Color(s)	black	blue	red	orange
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540816176	3342540816183	3342540816190	3342540816206

Reference(s)	R074AA21	R074AA22	R074AA23	R074AA24
				
Length	200 m	200 m	200 m	200 m
Color(s)	white	yellow	black	blue
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540816275	3342540816282	3342540816299	3342540816305

Reference(s)	R074AA25	R074AA26	R074AA28
			
Length	200 m	200 m	500 m
Color(s)	red	orange	white
Made in	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years
Inner Pack Count	1	1	1
Quantity Per Box	1	1	1
EAN	3342540816312	3342540816329	3342540816343

---

Related product(s) I'D® S  
I'D® EVAC