


Univers	Professional
Type	Verticality
Category	Ropes
Subcategory	Low stretch kernmantel ropes



## AXIS 11 mm With One Sewn Termination

The AXIS 11 mm low stretch kernmantle rope with sewn termination is designed for use with an ASAP or ASAP LOCK mobile fall arrester and an ASAP'SORBBER or ASAP'SORBBER AXESS energy absorber. It has a sewn termination with a protective sheath that helps keep the connector in position, meeting the requirements of the EN 12841 European standard for fall protection. The standard diameter provides a good grip for easier handling. EverFlex technology provides great flexibility and consistent performance over time. The rope is available in six lengths.



The sewn termination with protective sheath helps keep the connector in position and facilitates handling.

EverFlex technology provides great flexibility over time and under a variety of conditions (water, dust, mud), allowing it to maintain consistent handling and optimal performance with devices.

---

Short Description    Low stretch kernmantle rope with sewn termination for use with ASAP and ASAP LOCK mobile fall arresters

---

Selling Points

- Rope with a sewn termination, meeting the requirements of the EN 12841 standard when used with an ASAP or ASAP LOCK mobile fall arrester and an ASAP'SORBBER or ASAP'SORBBER AXESS energy absorber
- The standard diameter provides a good grip for easier handling
- Consistent performance over time:
  - Construction with nylon core and specially-braided polyester sheath
  - EverFlex technology provides great flexibility over time and under a variety of conditions (water, dust, mud), allowing it to maintain excellent handling and optimal performance with devices
- Rope with a sewn termination that has a protective sheath to help keep the connector in position and facilitate handling
- Space for individual identification markings on the plastic sheath to track the equipment throughout its lifespan
- Standard lengths: 10, 20, 30, 40, 50, and 60 m

---

Specification

- Diameter: 11mm
- Material(s): Polyester, nylon
- Certification(s): CE EN 1891 type A, NFPA 2500 Technical Use
- Weight per meter: 82g
- Strength with sewn termination: 22kN
- Impact force (factor 0,3): 5,2kN
- Number of factor 1 falls: 12
- Construction: 32 carrier
- Percentage of sheath: 41%
- Static elongation: 3%

---

## Specifications by reference

Reference(s)	R074BB00	R074BB01	R074BB02	R074BB03
Length	10 m	20 m	30 m	40 m
Color(s)	White	White	White	White
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	3	3	2	2
EAN	3342540854826	3342540855151	3342540855168	3342540855175

Reference(s)	R074BB04	R074BB05
Length	50 m	60 m
Color(s)	White	White
Made in	CZ	CZ
Guarantee	3 years	3 years
Inner Pack Count	1	1
Quantity Per Box	2	1
EAN	3342540854833	3342540854840

## Related product(s)

ASAP®  
ASAP® LOCK  
ASAP'SORBER  
ASAP'SORBER AXESS  
OK  
Bm'D  
OXAN