



Univers	Professional
Type	Verticality
Category	Mobile fall arresters
Subcategory	Ropes for mobile fall arresters



## AXIS 11 mm Rope With Two Sewn Terminations


The AXIS 11 mm low stretch kernmantle rope with two sewn terminations is designed for use with an ASAP or ASAP LOCK mobile fall arrester and an ASAP'SORBBER or ASAP'SORBBER AXESS energy absorber. It has two sewn terminations with a protective sheath that helps keep the connector in position, allowing it to meet the requirements of the EN 353-2 European standard for fall protection. The standard diameter provides a good grip for easier handling. EverFlex technology provides great flexibility and consistent performance over time. The rope is available in six lengths.



The AXIS 11 mm static rope with two sewn terminations is designed for use with an ASAP or ASAP LOCK mobile fall arrester.



The protective sheath helps keep the connector in position and facilitates handling.



EverFlex technology provides great flexibility over time and under a variety of conditions (water, dust, mud), allowing it to maintain consistent handling and optimal performance with devices.

---

Short Description    Low stretch kernmantle rope with two sewn terminations for use with an ASAP or ASAP LOCK mobile fall arrester

---

Selling Points

- Rope has two sewn terminations, meeting the requirements of the EN 353-2 and GBT 24537 standards when used with an ASAP or ASAP LOCK mobile fall arrester and an ASAP'SORBBER or ASAP'SORBBER AXESS energy absorber
- The standard diameter provides a good grip for easier handling
- Consistent performance over time:
  - Construction with nylon core and specially-braided polyester sheath
  - EverFlex technology provides great flexibility over time and under a variety of conditions (water, dust, mud), allowing it to maintain excellent handling and optimal performance with devices
- Rope with two sewn terminations, each with a protective sheath to help keep the connector in position and facilitate handling
- Space for individual identification markings on the plastic sheath to track the equipment throughout its lifespan
- Standard lengths: 10, 20, 30, 40, 50, and 60 m

---

Specification

- Diameter: 11mm
- Material(s): Polyester, nylon
- Certification(s): CE EN 1891 type A, meets the requirements of the EN 353-2 and GBT 24537 standards
- Weight per meter: 82g
- Strength with sewn termination: 22kN
- Construction: 32 carrier
- Percentage of sheath: 41%
- Static elongation: 3%

---

## Specifications by reference

Reference(s)	R074CB00	R074CB01	R074CB02	R074CB03
Length	10 m	20 m	30 m	40 m
Color(s)	White	White	White	White
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	3	3	2	2
EAN	3342540854857	3342540854864	3342540854871	3342540854888

Reference(s)	R074CB04	R074CB05
Length	50 m	60 m
Color(s)	White	White
Made in	CZ	CZ
Guarantee	3 years	3 years
Inner Pack Count	1	1
Quantity Per Box	2	1
EAN	3342540855090	3342540855106

## Related product(s)

ASAP®  
ASAP® LOCK  
ASAP'SORBBER  
ASAP'SORBBER AXESS  
OK  
OXAN