

Specialties



Classe	Tension max. d'utilisation COURANT ALTERNATIF
00	500 V
0	1 000 V
1	7 500 V
2	17 000 V
3	26 500 V
4	36 000 V



Catégorie	Résistant à
A	Acide
H	Huile
Z	Ozone
R	Acide, Huile, Ozone
C	Très basse température

Electric Related



The +

CLASS 0 - AZC
High dielectric protection.
Ergonomic shape.
Lightly powdered to facilitate donning and removal

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
8053	7		50
8054	8		50
8055	9		50
8056	10		50
8057	11		50

SALES PACKAGING



Individual polybag

DESCRIPTION

Insulating natural rubber gloves, cut edges.
The ergonomic shape of the glove and its slightly powdered interior makes it easy the donning and doffing.
The natural rubber provides dielectric properties, while our technique and expertise allow us to make gloves as thin as possible in order to offer the maximum level of the dexterity to the users.
Recommended for use with leather overgloves to provide mechanical protection.
Length: 36cm

SECTORS

- Manufacture of electrical and electronic equipment and machines
- Energy (production and distribution)
- Maintenance

APPLICATIONS

Electrical work, live working
Max operating voltage : 1000v
Proof test voltage : 5000v

TECHNICAL FEATURES

Color	Ecru
Shape	Glove
Gloves environment	Dry environment
Glove type	Dipping
Support material	Natural latex honey color
Tempered glove structure	Non supported
Interior finishing	Powdered
Support finition	Smooth
Type Of Cuff	Straight cut
Length - mm	360

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/11671-02/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. III

EN420:2003 + A1:2009

General requirements for protective gloves

EN60903:2003 + CEI 60903:2014

Electrical insulating gloves



Classe 0 catégorie AZC