

Specialties




Classe	Tension max. d'utilisation COURANT ALTERNATIF
00	500 V
0	1 000 V
1	7 500 V
2	17 000 V
3	26 500 V
4	36 000 V



Catégorie	Résistant à
A	Acide
H	Huile
Z	Ozone
R	Acide, Huile, Ozone
C	Très basse température

Electric Related



The +

CLASS 2 - AZC
High dielectric protection
Ergonomic shape
Lightly powdered to facilitate donning and removal

PURCHASE PACKAGING

Réf.	Taille	Sachet	Carton
8208	8	1	15
8209	9	1	15
8210	10	1	10
8211	11	1	2,50

SALES PACKAGING



Individual pack

DESCRIPTION

Insulating natural rubber gloves, cut edges.
The ergonomic shape of the glove and its slightly powdered interior makes it easy the donning and doffing.
The natural rubber provides dielectric properties, while our technique and expertise allow us to make gloves as thin as possible in order to offer the maximum level of the dexterity to the users.
Recommended for use with leather overgloves to provide mechanical protection.
Length: 36cm

SECTORS

Manufacture of electrical and electronic equipment and machines

Energy

Maintenance

APPLICATIONS

Electrical work, live working
Max operating voltage : 17000v
Proof test voltage : 20000v

TECHNICAL FEATURES

Color	Ecru	Length - mm	360
Shape	Glove		
Environment	Dry environment		
Glove type	Dipping		
Support material	Natural latex honey color		
Tempered glove structure	Non supported		
Interior finishing	Powdered		
Support finition	Smooth		
Type Of Cuff	Straight cut		

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/11606-01/E00-00**

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EN420:2003 + A1:2009

EN60903:2003 + CEI 60903:2014



Classe 2 - catégorie AZC

EPI CAT. III

General requirements for protective gloves

Electrical insulating gloves

RETAILER STAMP